

Ficha Técnica

Bota S3 SRC ESD Modelo HYBRID
Ref.MO100631

Descrição:

- A Monitor Hybrid é a nova Bota de segurança desportiva da linha dynamic fabricada com tecnologia de injeção;
- Sola em poliuretano de dupla densidade com uma dureza de Shore 50 A, que em combinação com a palmilha amovível SS 2.0 resulta num sapato incrivelmente confortável e almofadado com uma excelente absorção de energia;
- Este modelo possui atacadores convencionais;
- Possui uma Língua de fole;
- Interior com tecido que absorve a humidade;
- A gáspea é produzida em nubuck de vaca, com fita refletora no calcanhar e na gola;
- Anti-estático e anti-derrapante;
- Isenta de partes metálicas

Cor: Preto;

Tamanhos: 35 ao 47;

Norma: EN ISO 20345:2011 S3 SRC;



Biqueira em compósito



Anti-perfuração



Anti-estático



Ajuste Normal



EU TYPE EXAMINATION CERTIFICATE

intertek



APPROVED BODY 0362

The safety footwear detailed herein meets the criteria of an EU Type Examination in accordance with Annex V, including the applicable clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EU Declaration of Product Conformity you are

hereby licensed to mark the product(s) detailed in accordance with Article 17 of the PPE Regulation EU 2016/425

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



Issued to

: BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Authorised
Representative

: BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Manufacturer

: BASTAD GRUPPEN AB
Box 1031
262 21 Ängelholm
Sweden

Issue Date

: 02 September 2019

Expiry Date

: 02 September 2024

Certificate No.

: LECFI00376087

Product Reference(s)

: Micro
Hybrid

Description

: Construction	: PU injection
Toecap	: Composite toe
Midsole	: Kevlar
Last	: HN668
Sole	: PU/PU
Mould	: PU006
Test Report(s)	: See Technical Files
Size Range	: 36-47
Category	: S3 SRC

Assessor:

Date: 02/09/2019

Certification Manager:

Date: 02/09/2019

For and on behalf of ITS Testing Services (UK) Limited

intertek.com Registered in England No. 1408264 Registered Office: Academy Place, 1-9 Brook Street, Brentwood, Essex CM14 5NQ
This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.